

# Typical Performance Technical Data Sheet



Catalog No. T20LB42-225

## Characteristics

Phase	3
KVA	225
Primary	208Δ
Secondary	480Y/277
Conductor	Aluminum
Temp. Rise	80° C
Frequency	60 HZ
Taps	+2, -2 x 3.5%
ESS	No
Insulation	220° C
Weathershield	WS-16
Wall Bracket	NONE
Weight (lbs)	2275
Sound (dB)	55


## Typical Performance @ 100° C

Regulation @ 100% PF	1.0%
Regulation @ 80% PF	2.9%
Impedance	3.7%
No Load Losses (W)	527
Full Load Losses (W)	2,453

## AMP Ratings

Line In (Primary) @ 208V	625 A
Load (Secondary) @ 480V	271 A


## Wiring Diagram -23C



VOLTS	CONNECTIONS	LINE LEADS
223	2 TO 3	X1, X2, X3
215	2 TO 5	X1, X2, X3
208	3 TO 4	X1, X2, X3
201	4 TO 5	X1, X2, X3
193	5 TO 6	X1, X2, X3
480Y/277		H0, H1, H2, H3

## Notes

All units are UL listed and are designed in accordance with applicable NEMA, ANSI and IEEE standards.  
Transformers are dry-type AA, ventilated NEMA 2 enclosure.  
If a weathershield is indicated above this transformer can be converted to a NEMA 3R enclosure.  
Transformers are floor mounted. Wall mounting bracket kit if shown above is optional and is supplied as a separate accessory.  
Paint color is ANSI 61.



Outline No: 08A3309

Meets 10 CFR 431(DOE 2016) Efficiency  
Dry Type Transformer General Purpose

© 2017 Electro-Mechanical Corporation

For reference only  
Subject to change without notice