

# Typical Performance Technical Data Sheet



## Catalog No T48SF2Y-225-K20

### Characteristics

Phase	3
KVA	225
Primary	480Δ
Secondary	208Y/120
Conductor	Aluminum
Temp. Rise	115° C
Frequency	60 HZ
Taps	Insult Factory
ESS	Yes
Insulation	220° C
Weathershield	Insult Factory
Wall Bracket	Insult Factory
Weight (lbs)	Insult Factory
Sound (dB)	58


### Typical Performance @ Consul

Regulation @ 100% PF	0.0%
Regulation @ 80% PF	0.0%
Impedance	0.0%
No Load Losses (W)	0
Full Load Losses (W)	0

### AMP Ratings


Line In (Primary) @ 480V	271 A
Load (Secondary) @ 208V	625 A

### Wiring Diagram -18A



### Notes

All units are UL listed and are designed in accordance with applicable NEMA, ANSI and IEEE standards.  
Transformers are dry-type AA, ventilated NEMA 2 enclosure.  
If a weathershield is indicated above this transformer can be converted to a NEMA 3R enclosure.  
Transformers are floor mounted. Wall mounting bracket kit if shown above is optional and is supplied as a separate accessory.  
Paint color is ANSI 61.



Outline No: 08A3228

Meets 10 CFR 431(DOE 2016) Efficiency  
Dry Type Transformer General Purpose

© 2017 Electro-Mechanical Corporation

For reference only  
Subject to change without notice